ONKYO.

TX-NR7100 9.2-Channel THX Certified Network A/V Receiver



A richer, better life in 8K Ultra HD

Turn your home into a living media sanctuary with 9.2-channel Dynamic Audio Amplification (DAA) supporting 3D surround-sound and powered multizone audio together with the SMART AV Receiver[™] suite for effortless voice-controllable entertainment via a Google Assistant or Amazon Alexa enabled device. HDMI[®] supports 8K/60p and dynamic HDR (including HDR10+ and Dolby Vision[™]) passthrough to compatible TVs, projectors, or gaming monitors connected via eARC-ready Main Out. Be overwhelmed by the hyper-realistic THX® Certified Select reference experience, and explore the master-quality IMAX® Enhanced film library. Unique functions such as Front-to-Height stereo switching for ambient background listening, DSP vocal/dialog enhancement, and practical GUI functions simplify everyday operation. Whether you're gaming, watching a favorite TV series, or streaming Hi-Res Audio, a richer emotional life awaits inside the Onkyo signature sound.

PRODUCT HIGHLIGHTS

- 185 W/Ch THX[®] Certified Select DAA system - IMAX $^{\otimes}$ Enhanced certified for immersive signature sound by DTS:X $^{\otimes}$
- 5.2.4-ch/7.2.2-ch Dolby Atmos[®] and DTS:X playback
- Supports Dirac Live® Room Correction · AccuReflex phase-matching solution for Atmos-enabled
- SMART AV Receiver[®] Works with Sonos⁵¹, Chromecast built-in[®], AirPlay 2, and DTS Play-Fl[®]; includes Spotify[®], Amazon Music HD¹², TIDAL, Deezer, and Tuneln streaming services³
 Works with Ok Google or Alexa^{*4}
- Stream over 5 GHz/2.4 GHz dual-band Wi-Fi® supporting the 802.1 I ac standard¹⁵
- HDMI[®] inputs 1-3 and Main/Sub outpus su 8K/60p(4:2:0/10-bit), 8K/30p(4:4:4/10-bit), 4K/120p(4:4:4/10-bit) video pass through support
- HDMI terminals¹⁹ support HDR10+, Dolby Vision and BT.2020 color; VRR (Variable Refresh Rate), ALLM (Auto Low Latency Mode), and QFT (Quick Frame Transport) passthrough; eARC (Main Out), and HDCP 2.3 • HDMI Sub/Zone 2 Out for media transmission to a
- second display
- Send or receive audio via Bluetooth[®] wireless technology (RX mode: SBC/AAC, TX mode: SBC/Qualcomm[®] aptX[™]/ aptX HD)
- Refined chassis, HDMI board, DAC, Digital/Analog inputs,
- Reined chastis, mDrin Doard, DAC, Digtal/Analog inputs, power-amp grounds and power lines
 5.2-ch Main + Powered Zone 2 + Powered Zone 3 speakers support synced/independent D/A audio playback (including HDMI/SPDIF/NET*)
- Zone 2/Zone B line-out⁷ (analog RCA) supports synced or independent D/A playback¹⁸ on compatible audio systems or headphone docks

AMPLIFIER FEATURES

- 185 W/Ch (6 $\Omega,$ 1 kHz, 10% THD, 1 channel driven), 170 W/Ch (6 $\Omega,$ 1 kHz, 1% THD, 1 channel driven, IEC) THX Certified Select
- Certified for IMAX Enhanced Onkyo Dynamic Audio Amplification (DAA)
- Discrete 2-stage non-phase-shift amplifier circuitry
- Custom High-Current Low-Noise Power Transformer
- Large custom-made audio-grade power capacitors
- · Strengthened power-supply line supports high-current dynamics
- Refined chassis, HDMI board, DAC, Digital/Analog inputs, power-amp grounds and power lines
- · Isolated network module reduces high-frequency signal interference on audio circuitry
- · High current capability drives 4-ohm loads through 9 channels
- ecision 192 kHz/24-bit D/A conversion for Hi-Res Audio
- VLSC[™] (Vector Linear Shaping Circuitry) noise filtering (Front L/R) • PLL (Phase Locked Loop) anti-jitter technology for SPDIF audio
- Independent tone controls for all channels (excluding Zone 3)

- **VIDEO & AUDIO SUPPORT**
- Supports features defined in HDMI 2.1st specification including 8K/60p(4:4:4/12-bit⁻¹⁰, 4:2:2/12-bit⁻¹⁰, 4:2:0/10-bit⁻¹¹), 8K/30p(4:4:4/12-bit⁻¹⁰, 4:4:4/10-bit⁻¹¹, 4:2:2/12-bit⁻¹¹, 4:2:0/12-bit), 4K/120p(4:4:4/12-bit⁻¹⁰, 4:4:4/10-bit⁻¹¹, 4:2:2/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹⁰, 4:4:4/10-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹⁰, 4:4:4/10-bit⁻¹¹, 4:2:0/12-bit), and CS/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit⁻¹¹, 4:2:0/12-bit), 4K/20p(4:4:4/12-bit), 4K/20p(4:4:4/12-
- Master Audio® decoding
- Dolby Atmos Height Virtualizer 3D sound processing
- Dolby Surround[®] and DTS[®] Neural:X 3D upmixing technologies Hi-Res Audio playback via network and USB including DSD256, DSD128, DSD64 (DSDIFF/DSF) and 192 kHz/24-bit FLAC, ALAC, WAV (RIFF), and AIFF⁺¹²
- SACD (Super Audio CD) playback via HDMI (2.8 MHz 2-ch/multichannel)
- IMAX Enhanced certified for immersive signature sound by DTS:X • THX® listening modes for movies, music, and gar
- · Theater-Dimensional virtual surround-sound function
- Sound optimization for games (Rock, Sports, Action, and RPG) · Direct Mode and Pure Audio Mode

NETWORK FEATURES

- SMART AV Receiver multi-room platform with integrated streaming services, voice assistant support, and control via remote apps
 Fast quad-core SoC supports 802.11ac (2x2 MIMO) Wi-Fi
- \bullet Works with Sonos for the Sonos Home Sound System with Sonos app $^{\ast_{13}}$
- Works with Alexa supporting multi-room music^{*1}
- Works with Ok Google and Chromecast built-in
- Supports Apple AirPlay 2 enabling Siri voice control
- DTS Play-Fi multi-room audio via Onkyo Music Control App*13
- Control and manage multiroom playback with Onkyo Controller app^{*13}
- Roon Tested certification for the Roon Core
- · IP Control for AVR setup via PC and integration into a home automation system

CONNECTION FEATURES

- 7 HDMI inputs (I front), 2 outputs (Main Out [eARC], Sub/Zone 2 Out)
- I component video input (assignable)
- 2 composite video inputs (assignable)
- · 2 digital audio inputs (optical and coaxial, assignable)
- 6 analog RCA audio inputs (assignable) · 3.5 mm mini-stereo analog input (front)
- · I phono input with built-in MM phono equalize
- 3.5 mm mic input for room acoustic correction setup
- 6.35 mm headphone jack
- · I Front L/R speaker pre-out
- 2 subwoofer pre-outs
- Zone 2/Zone B analog RCA line-level out
- 9 speaker binding posts
- I0BASE-T/I00BASE-TX Ethernet terminal for network connection
- USB input (DC 5 V/I A) for audio playback (rear)
- RS-232C serial input and IR input for infrared repeaters
- 12 V trigger output (Main, 100 mA, assignable)
- AC inlet for detachable IEC power cord

ADVANCED FEATURES

- Supports Dirac Live Room Correction
- Bluetooth wireless technology supports audio reception from mobile devices and PC, audio transmission to supported headphones (RX mode: SBC/AAC, TX mode: SBC/aptX/aptX HD)
- Advanced Music Optimizer™ improves compressed audio playback quality · Wake on Play standby for Bluetooth and Network with auto
- input-switching
- Dedicated Zone 2 D/A converter supports simultaneous playback of independent sources (HDMI/SPDIF/NET)
- S.2.-Ch + Zone 2 speaker outputs enable 7.2-ch + Zone 2 / 5.2.2-ch + Zone 2 / 5.2-ch + Zone 2 + Zone 3 speaker connection and switching⁴¹²
- Zone 2 line-out" (analog RCA) connects compatible audio systems for independent D/A playback (HDMISPDIF/NET") Zone B line-out" (analog RCA) connects compatible wireless headphone transmitters for synced playback with MAIN Zone¹⁸

- · Front L/R pre-out supports external power amp connection · Vocal Enhancer boosts vocals/dialog audibility via remote control or
- Switch Front L/R speakers to Height 1/Height 2/Surround/Surround Back with Stereo Assign Mode¹¹⁵ for BGM listening
- My Input Volume one-touch startup volume assignment to
- individual inputs
- High-definition GUI with overlaid OSD over HDMI • 4K to 8K, 1080p to 8K/4K upscaling and 480i to 480p deinterlacing

uire a firmware update. *15 Speaker-switching capabilities depend on . *16 Max. 400 ms (5 ms steps) at 96 kHz, and max. 200 ms (5 ms

- over HDMI OSD function shows Audio, Video and Network information
- FM and DAB/AM tuner with 40 random station memory presets
- Crossover adjustment for each channel (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (up to 500 ms in 5 ms steps at 48 kHz*16) Various standby modes and HDMI pass-through
- 3-Mode display dimmer (Normal/Dim/Dimmer)
- Optional rack-mounting kit (IRK-155-3D) *I Requires a Sonos Connect or Port (sold separately). Connection of 1–3 Sonos devices is supported with volume control enobled via the Sonos app for iOS and Android" devices. *2 Amazon Music HD is supported via DTS Play-Fi. *3 Streaming service availability may vary by region. An account and subscription may be required for some streaming service availability may vary by region. An account and subscription may be required for some streaming service availability may vary beneform. An account and subscription may be required for some streaming service availability may vary steeders or smartphone. Interopretability with streaming service devices. such as a smart spectro and the country or region. *5 Some caunties or regions have regulations that affect wireless signal strength and use of W-Fi channels. *6 Zon 3 Supports andog M-ET orly. In Zone 3 L HDM and a SDPI Support 2-A hr CM audio signals only, and HDM audio is supported via HDMI inputs 1–3. Simultaneous ployback for all hubbl support 2-A hr CM signals only, and simultaneous ployback for all hubbl support 2-A hr CM signals only, and simultaneous ployback for all hubbl support 2-A hr CM signals only and area. *9 AF exe and the XMI support 2-A hr CM signals only and the XMI audio is available avail oscures is enabled. When set to Zone B mode, encoded and 2-A hr CM audio ployback for all hubbl.

steps) at 192 kHz

THX® Certified Select cinema-reference sound

THX Certified Select guarantees the same reference volume of a commercial cinema in rooms where the screen-to-seat distance is about 3.5 m. Certified receivers must pass 2,000 bench-tests in 75 categories

Discover the IMAX[®] experience

IMAX® Enhanced uses DTS:X® technology optimized for the IMAX signature experience and reproduces the full dynamic range of IMAX theatrical mixes. IMAX Mode delivers IMAX

Enhanced content as the filmmakers intended. IMAX Enhanced films are available to stream or own on Ultra HD Blu-rav[™]



Welcome to the 8K Ultra HD experience

Features defined in HDMI® 2.1 specification enable 8K/60p video passthrough to your compatible display. As well as HDR10 and HLG, HDR10+ and Dolby Vision[™] formats optimize brightness, contrast, and color scene-by-scene or frame-by-frame. All HDMI terminals support HDCP 2.3, while eARC on Main Out passes encoded multichannel audio (including Dolby Atmos® or DTS:X) from your compatible TV's tuner, video streaming apps, or connected media players to the AVR for amplification. QMS (Quick Media Switching) for movies and video eliminates the delay that can result in a blank screen before content is displayed.

Note: Features defined in HDMI 2.1 specification, HDR10+, and passthrough capabilities described are supported on HDMI inputs 1–6, Main Out, and Sub/Zone 2 Out in Sub Mode output.

New enhancements for gamers

Transform your playtime with 3D surround-sound and gain the winning edge with new gamer-friendly features defined in HDMI 2.1. VRR (Variable Refresh Rate) eliminates lag, stutter, and frame-tearing for fluid gameplay. ALLM (Auto Low Latency Mode) optimizes latency from source to screen while QFT (Quick Frame Transport) limits lag for a smoother experience.

SMART AV Receiver[™] multi-room audio streaming

SMART AV Receiver shares audio around your home. It includes Amazon Music HD*, Spotifv®, TIDAL, Deezer, and Tuneln, and works with Ok Google or Alexa. Share entertainment via Works with Sonos, AirPlay 2, DTS Play-Fi®, and Chromecast built-in.



* Amazon Music HD is supported via DTS Play-Fi.

Works with Sonos

Expand your Sonos Home Sound System by pairing this AVR with up to three Sonos Connect or Port* devices. The receiver ties into the Sonos ecosystem, waking, changing inputs, and playing at the desired volume on command from the Sonos app*.

* Sonos Connect and Port sold separately. Sonos app available free for iPhone and iPad from the App Store, and for Android[™] devices on Google Play Store.

Chromecast built-in[™] works with Ok Google

Stream music from your smartphone, laptop, or PC to the receiver via Chromecast built-in and control playback from Chromecast-enabled apps from iPhone, iPad, Android[™] phone or tablet, Mac or Windows[®] PC, or Chromebook[™]. Cue, play, and control audio on this and other supported devices just by using your voice.

Works with Alexa

Alexa lets you use your voice to control the A/V receiver by speaking commands through an Alexa device. Whether you want to listen to music, radio stations, or podcasts, all you have to do is ask. It also supports multi-room music" played on multiple devices. * Multi-room music may require a firmware update

Dolby Atmos and DTS:X - celebrate a new world of sound

Dolby Atmos and DTS:X translate 3D soundtracks from the studio mixing desk to your room. Sounds are no longer tied to specific channels, and are free to move around and above your audience, placing them at the heart of the action. The TX-NR7100 supports 5.2.4-ch and 7.2.2-ch speaker layouts.

Enjoy 3D sound from any speaker layout

Dolby Atmos Height Virtualizer delivers 3D sound through any listener-level speaker layout. The technology works independently or with the Dolby Surround® upmixer to create a 3D sound-field.

Dirac Live® Room Correction

Dirac Live analyzes your audio system and listening environment by examining acoustic data measured by microphone and detecting deficiencies. It corrects both the timing and amplitude aspects of sound DIRAC colorations using a mixed-phase correction filter throughout the listening area, not just a particular zone. Dirac Live automatically calibrates sound in your room using a smartphone or tablet" application and setup mic. Dirac Live unlocks your loudspeakers' full potential in any listening space and delivers a uniquely pristine listening experience. * Device must be connected to the internet and the same network as your AVR

5 GHz/2.4 GHz dual-band Wi-Fi® supports the 802.1 lac standard*

A powerful quad-core SoC (System on a Chip) performs multiple processing tasks at once. It evolves network functions and supports the 802.11 ac (2x2 MIMO) standard for stable multi-room audio streaming.

* Note: some countries or regions have regulations that affect wireless signal strength and the use of Wi-Fi channels.

Bi-directional Bluetooth® wireless technology

This AVR can send and receive audio via Bluetooth wireless technology. Stream from your device to the receiver using SBC or AAC codecs, or transmit audio playing through the aptX HD codecs including 24-bit audio over aptX HD. Note: subborts MAIN Zone source transmission (excludes Chromecast built-in a Works with Alexa). Lossless 24-bit audio requires headphones supporting aptX HD.

Clearer dialog at the touch of a button

Vocal Enhancer solves the problem of inaudible dialog in movies and TV programs by using DSP algorithms to elevate vocal frequencies in the soundtrack. The effect level can be raised or lowered using keys on the remote control

Three-Zone Whole Home Audio

Manage playback in up to three rooms using the Onkyo Controller app. This 9.2-ch AVR has a Zone 2 DAC supporting amplified D/A audio distribution (including HDMI, SPDIF, and NET) via Zone 2 and Zone 3 speaker posts, and supports layouts including 5.2.2-ch Main + Zone 2 or 5.2-ch + Zone 2 + Zone 3.

Note: Zone 3 supports analog/NET only. Zone 2 HDMI audio available on inputs 1–3. HDMI and SPDIF support 2-ch PCM audio signals only.

Multi-function Zone 2/Zone B line-out

Analog RCA line-out supports two Zone audio modes. Zone 2 supports active speaker or hi-fi system connection. Sync a source in MAIN and Zone 2, or play two unique D/A sources simultaneously. Zone B suits wireless headphone docks. Enjoy MAIN Zone audio through your wireless headphones.

Relax with Stereo Assign Mode

Stereo Assign Mode switches playback from Front to Height I, Height 2, Surround, or Surround Back speakers (depending on your layout). It's ideal for ambient background listening.

Connections for custom installations

A 12 V trigger output syncs operation with an external component, such as a power amp, while IR input connects an IR repeater. Ethernet supports IP control for home automation and AVR configuration via PC browser. RS-232C control and OSD output are supported. Rack-mount kit is optionally available.

SPECIFICATIONS

Amplifier Section	
Power output (All channe	
	185 W/Ch
	(6 Ω, 1 kHz, 10% THD, 1-ch driven)
	170 W/Ch
	(6 Ω, 1 kHz, 1% THD, 1-ch driven, IEC)
Dynamic power	250 W (3 Ω, Front)
	220 W (4 Ω, Front)
	130 W (8 Ω, Front)
THD+N (Total Harmonic	: Distortion + Noise)
	0.08% (20 Hz–20 kHz, half power)
Input sensitivity and impe	dance
1	200 mV rms/47 kΩ (Line)
	3.5 mV rms/47 kΩ (Phono MM)
Rated RCA output level a	
	I V rms/470 Ω (Subwoofer pre-out)
	200 mV rms/470 Ω (Zone 2/Zone B line-out)
Frequency response	10 Hz–100 kHz/+1 dB,
	-3 dB (Direct/Pure Audio)
Tone control	±10 dB, 20 Hz (Bass)
	±10 dB, 20 kHz (Treble)
Signal-to-noise ratio	106 dB (Line, IHF-A)
	80 dB (Phono, IHF-A)
Speaker impedance	4–16 Ω
Video Section	
Input sensitivity/output le	
Video	I.0 Vp–p/75 Ω (Component Y)
	0.7 Vp–p/75 Ω (Component Pb/Pr)
	I.0 Vp–p/75 Ω (Composite)
Tuner Section	
Tuning frequency range	
	174.000 MUL- 0000 MUL-
DAB (Europe)	174.928 MHz–239.2 MHz
FM	87.5 MHz-108 MHz
FM AM (Asia & Oceania)	522 kHz–1,611 kHz
AM (Asia & Oceania)	522 kHz–1,611 kHz 530 kHz–1,710 kHz
AM (Asia & Oceania)	522 kHz–1,611 kHz 530 kHz–1,710 kHz
AM (Asia & Oceania) FM/DAB/AM preset mem	522 kHz–1,611 kHz 530 kHz–1,710 kHz ory
AM (Asia & Oceania) FM/DAB/AM preset mem General	522 kHz=1,611 kHz 530 kHz=1,710 kHz ory 40 stations
AM (Asia & Oceania) FM/DAB/AM preset mem General	522 kHz–1,611 kHz 530 kHz–1,710 kHz ory
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 VV
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle)	522 kHz=1,611 kHz 530 kHz=1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle)	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating 760 W 75 W dby
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan Dimensions (W x H x D)	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W 435 x 173.5 x 379.5 mm
	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan Dimensions (W x H x D) Weight	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W 435 x 173.5 x 379.5 mm
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan Dimensions (W × H × D) Weight CARTON	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W 435 x 173.5 x 379.5 mm 10.4 kg
AM (Asia & Oceania) FM/DAB/AM preset mem General Power supply Power consumption (ope Power consumption (idle) Power consumption (stan Dimensions (W x H x D) Weight	522 kHz-1,611 kHz 530 kHz-1,710 kHz ory 40 stations AC 220-240 V~, 50/60 Hz rating) 760 W 75 W dby) 0.15 W 435 x 173.5 x 379.5 mm 10.4 kg

Power cord • Indoor DAB/FM antenna • AM loop antenna Speaker setup microphone • Quick Start Guide • Remote controller

0 Ô 00 00 0 C€HLZ ۲

Text on receiver may vary with region

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. THX and the THX Logo are the property of THX Ltd, registered in the U.S. and other countries. Dolby, Dolby Atmos, Dolby Vision, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited. DTS, the Symbol. DTS and the Symbol together, DTSX and the DTS X logo, DTS NtrualX and the DTS NtrualX (logo, DTS NeuralX and the DTS NeuralX) and the DTS NeuralX and the NeuralX NeuralX and the Countries SecondY and ther reademarks of Apple Inc. Cosple Android, Inc. The Buetoath® word mark and lopes are countered and ther reademark of Apple Inc. Cosple Android, Inc. The Vister Allance. The Vister NEI CEXTREME ProductS displaying the Hi-Res Audio logo to countries. SpotY and the SpotY logo are trademarks of the SpotIfy Group, registered in the U.S. and other countries. SpotY and the SpotIfy logo are trademarks and all related logos are trademarks of Amazon. Inc. or is affilia





Note: in Zone 2 mode, HDMI audio is available on inputs 1–3 and SPDIF and HDMI support 2-ch PCM signals only. In Zone B mode, encoded and 2-ch PCM audio playback for all inputs is enabled in MAIN and Zone B.

Supplied Accessories

AAA (R03) batteries x 2